

ELIZA



General data:

Mounting type:	mounting base
Luminaire body:	aluminum
Operating temperature range:	from -20°C to +45°C
Lifetime L80B10:	100 000h
Ingress protection IP:	IP65
Impact protection IK:	IK08

Optical data:


Light distribution:	symmetrical, street, park
Contains light source:	yes
Optical system:	lens
Material:	PMMA
Protection class:	I

Lighting data:

Colour rendering index:	CRI>70
Type of source:	LED

Electrical data:

Nominal voltage:	220-240V AC
Nominal frequency:	50-60Hz
Dimming:	ON-OFF
supply box:	inside the luminaire
wiring:	through
tolerance of luminous flux:	SDCM<3
colour tolerance SDCM:	+/-10%
light emission:	direct



The economical outdoor light pole Eliza is the perfect choice for those seeking a stylish, durable, and cost-effective lighting solution. It is suitable for both private gardens and commercial spaces, enhancing the aesthetics and functionality of the illuminated areas.

C - colour

L - lenses to choose:

02 - asymmetric

floodlighting


distribution

03 - street lighting

distribution

04 - park lighting

distribution



Catalogue code	Luminaire light flux	Power	Effectiveness	Color temperature	Dimensions
94 33.130LC	1844lm	12W	154 lm/W	3000K	1000mm
94 33.140LC	1920lm	12W	160 lm/W	4 000K	1000mm

Accessories

Ground foundation Type B

cod number 90.16.13

