

Recessed floor light - Peacock, 2 W, 3,000 K, silver



Image similar

Prices

List price (VAT included)	109.95 EUR per 1
Minimum order quantity	1
Order step	1

Information

Order number	730459
EAN	4042943153005

Description

- Including 0.5 m connecting cable with protected connection socket

Features

RRP incl. VAT	109.95 EUR
Housing Material	Stainless steel
Housing Material	Aluminium
Housing Color	Silver
Frequency	50 / 60 Hz
Primary Connection	Connection box IP67
Load Force max.	5 kN
Light Source	Light source not changeable
Light Source	LED
Luminous Efficiency	75.0 lm/W
Light Distribution	Symmetric
Colour Consistency	5 SDCM
Switching Cycles	100000
Product weight	339 g
Power Supply Unit incl.	Yes
Power Consumption	3 kWh/1000h
Power Factor	0.90
Working Temperature	-20 to 40 °C
Storage Temperature	-10 to 60 °C
Mounting Type	Installation mounting
Mounting Location	Outside
Mounting Area	Ground installation
Rated Input Voltage	220-240 V/AC
Rated Input	2.0 W
Dimmable	No
Motion Detector	No
Power Supply Unit Changeable	No

Protection Class	Protection class II /protective insulation
Lightcolor	Warm white (WW)
Color Temperature	3000 K
Colour Rendering Index (Ra)	80
Rated Luminous Flux	150 lm
Light direction	Top
Rated Angle of Reflection	30 Degree
Height	43 mm
Diameter	58 mm
Cut Out Diameter	44 mm
Installation Depth	48 mm
IP Protection Class	IP 67
IK Protection Class	IK08
Functions	Walkable - 5 kN
Life Time L70 / B50	25000 h
Energy efficiency class	G

