


SR



General data:

Luminaire body:	aluminium
Mounting type:	ground fundation
Ingress protection IP:	65
Operating temperature range:	from -40°C to +40°C
Lifetime L80B10:	100 000h
Impact protection IK:	10

Electrical data:

Nominal voltage:	220-240V AC
Nominal frequency:	50-60Hz
Protection class:	I
Wiring:	through
Dimming:	ON-OFF, DALI
Power supply:	wewnętrzna oprawy

Optical data:


Optical system:	lens
Material:	PMMA
Light emission:	direct
Light distribution:	symmetrical

Lighting data:

Light source:	LED
Colour rendering index:	CRI>80
Colour tolerance SDCM:	SDCM<3
Tolerance of luminous flux:	+/-10%


The SR light pole represents a sophisticated combination of modern elegance and excellent functionality. Its minimalist geometric shape transforms it not only into an effective light source, but also into a unique design element of the outdoor space. The modern form of the SR light post not only perfectly meets lighting standards, but also creates a unique visual comfort.

Photometric body



C - colour

E- electronics
O- ON-OFF
D- DALI



Catalogue code	Luminaire light flux	Power	Effectiveness	Color temperature	Weight
9367.03EC	474lm	7W	72lm/W	3000K	4,4 kg
9367.04EC	504lm	7W	72lm/W	4000K	4,4 kg
9368.03EC	778lm	13W	64lm/W	3000K	4,4 kg
9368.04EC	828lm	13W	64lm/W	4000K	4,4 kg

Accessories

Ground foundation type B

code number: 90.16.07

