

UFO




General data:

Luminaire body:	aluminum
Mounting type:	on an adjustable holder, to the ground
Ingress protection IP:	66
Operating temperature range:	from -40° to +45°
Lifetime L80B10 :	100 000h
Impact protection IK:	07



Electrical data:

Nominal voltage:	220-240V AC; 24V DC
Nominal frequency:	50-60Hz; DC
Luminaire nominal power:	2W, 3W
Protection class:	I, III
Connection:	wire 3x1mm ²
Wiring:	through, standard
Connection wire:	0,5m
Dimming:	ON- OFF
Power supply:	inside the luminaire



Optical data:

Optical system:	lens
Material:	PC
Light emission:	direct
Light distribution:	symmetrical

Lighting data:

Light source:	LED
Luminous flux from luminaire 2W, 3W:	153 lm, 306 lm
Luminous efficacy from luminaire 2W, 3W:	146 lm/W
Colour temperature:	2700K, 3000K, 4000K (option: 6500K)
Colour rendering index:	CRI>80 (options: CRI>90)
Colour tolerance SDCM:	SDCM<3
Tolerance of luminous flux:	+/-10%


UFO is an outdoor luminaire with specialized optics designed to illuminate window recesses and facade elements. The luminaire distribute the light around the recess, creating a beautiful effect, giving lighting and decoration at the same time. The high protection class IP66 gives the luminaire high resistance to bad weather conditions, moisture and dust. Thanks to the adjustable handle, it is possible to precisely adjust the direction of the light beam.

L- beam angle
31-165°x3°

W - wiring
T - through
S - standard

C - colour

E- electronics
O- On-Off



Catalogue code	Luminaire light flux	Power	Color temperature	CRI/RA	Weight	Dimensions	Box dimensions
9182.02ELCW	134lm	2W	2700K	≥80	0,7 kg	Ø 90mm, H=75mm	200x200x200mm
9182.03ELCW	144lm	2W	3000K	≥80	0,7 kg	Ø 90mm, H=	200x200x200mm
9182.04ELCW	153lm	2W	4000K	≥80	0,7 kg	Ø 90mm, H=75mm	200x200x200mm
9183.02ELCW	268lm	3W	2700K	≥80	0,7 kg	Ø 90mm, H=75mm	200x200x200mm
9183.03ELCW	288lm	3W	3000K	≥80	0,7 kg	Ø 90mm, H=75mm	200x200x200mm
9183.04ELCW	307lm	3W	4000K	≥80	0,7 kg	Ø 90mm, H=75mm	200x200x200mm
9183.12OLCW	268lm	3W(24 V)	2700K	≥80	0,7 kg	Ø 90mm, H=75mm	200x200x200mm
9183.13OLCW	288lm	3W(24 V)	3000K	≥80	0,7 kg	Ø 90mm, H=75mm	200x200x200mm
9183.14OLCW	307lm	3W(24 V)	4000K	≥80	0,7 kg	Ø 90mm, H=75mm	200x200x200mm

Accessories

connector IP68 3-pole

catalogue code 124.00



embranchment IP67

catalogue code 90.10

