

xeno

3 YEARS
WARRANTY



EN

Adjustable recessed light fittings for exterior, equipped with COB LEDs, high efficiency, housing of die-cast aluminum electrostatically painted in mat white or dark grey, transparent tempered glass diffuser.

Supplied with IP65 connection box with three access cable glands.

Range of applications

General lighting in bathroom and other interior humid areas.

Exterior general lighting in soffits of buildings.

RO

Spoturi de încastrat orientabile pentru exterior echipate cu LED-uri COB, cu eficiență luminoasă mare, structură din aluminiu turnat sub presiune vopsit în câmp electrostatic alb mat sau gri închis, dispersor din sticlă temperată transparentă.

Dotate cu doză de derivație IP65, cu trei preșetupe de acces.

Aplicații

Iluminatul general în băi sau alte spații umede din interior.

Iluminatul general de exterior în copertinele clădirilor.

IT

Faretti da incasso orientabili per esterni equipaggiati con LED COB ad alta efficienza luminosa, corpo in pressofusione di alluminio verniciato a polveri bianco opaco o grigio scuro, diffusore in vetro temperato trasparente.

Forniti con scatola di connessione IP65 e tre pressacavi di accesso.



Campi di applicazione


illuminazione generale, bagni e altre aree umide in interni.

illuminazione esterna di pensiline e controsoffittature di edifici.

FINISHING AVAILABLE

MWH DG



Code	Finishing	LED type	Power	Input voltage	Driver	LED flux	System flux	CCT	CRI	Optics		Weight
9584	MWH	COB LED LUMENS	7W	220-240V AC	Included	816 lm	709 lm	3000K	80	39°	Ø95 mm	0,48 kg
9585	DG	COB LED LUMENS	7W	220-240V AC	Included	816 lm	709 lm	3000K	80	39°	Ø95 mm	0,48 kg
90033	MWH	COB LED LUMENS	7W	220-240V AC	Included	830 lm	717 lm	4000K	80	39°	Ø95 mm	0,48 kg
90034	DG	COB LED LUMENS	7W	220-240V AC	Included	830 lm	717 lm	4000K	80	39°	Ø95 mm	0,48 kg

