

xglow recessed



5 YEARS
WARRANTY



EN
Recessed light fittings equipped with COB LEDs.
Housing of die-cast aluminum, electrostatically painted.
Reflector of silver faceted polycarbonate.
Satin glass diffuser with round central element clear.
Optical system UGR<16.
Constant current LED driver delivered with the light fitting.
Range of applications
General or accent lighting in commercial areas, museums and other exhibition spaces, residential and recreational areas.
Domestic lighting.


RO
*Corpuri de iluminat încastrate echipate cu LED-uri COB.
Carcasa din aluminiu turnat, vopsită în câmp electrostatic.
Reflector din polycarbonat argintat și fațetat.
Dispersor din sticlă satinată cu element central circular transparent.
Sistem optic UGR<16.
Alimentator în curent constant livrat împreună cu corpul de iluminat.*
Aplicații
*Iluminatul general sau de accent în spații comerciale, muzee și alte spații de expunere, zone rezidențiale și zone de agrement.
Iluminatul domestic.*

IT
Apparecchi da incasso, equipaggiati con LED COB.
Corpo in alluminio pressofuso, verniciato a polveri.
Riflettore in polycarbonato argentato e sfaccettato.
Diffusore in vetro satinato con elemento centrale trasparente.
Sistema ottico UGR<16.
Alimentatore in corrente costante fornito con ogni apparecchio.
Campi di applicazione
Illuminazione generale o d'accento in musei, spazi espositivi, aree residenziali e ricreative.
Illuminazione domestica.

GLR01 RECESSED

FINISHING AVAILABLE

MWH/WH MBK/BK





| Code | Finishing | LED type | Power | Input voltage | Output current/voltage driver | Driver | LED flux | System flux | CCT | CRI | Optics | Weight |
|-----------------------|-----------|-------------|-------|---------------|-------------------------------|----------|----------|-------------|-------|-----|--------|-----------------|
| GLR01WW MWH/WH | MWH/WH | COB CITIZEN | 1x13W | 220-240V AC | 350 mA / 25-40V DC | Included | 1190 lm | 663 lm | 3000K | 90 | 20° | Ø80 mm, 0,19 kg |
| GLR01NW MWH/WH | MWH/WH | COB CITIZEN | 1x13W | 220-240V AC | 350 mA / 25-40V DC | Included | 1270 lm | 718 lm | 4000K | 90 | 20° | Ø80 mm, 0,19 kg |
| GLR01WW MBK/BK | MBK/BK | COB CITIZEN | 1x13W | 220-240V AC | 350 mA / 25-40V DC | Included | 1190 lm | 663 lm | 3000K | 90 | 20° | Ø80 mm, 0,19 kg |
| GLR01NW MBK/BK | MBK/BK | COB CITIZEN | 1x13W | 220-240V AC | 350 mA / 25-40V DC | Included | 1270 lm | 718 lm | 4000K | 90 | 20° | Ø80 mm, 0,19 kg |

GLR02 RECESSED TRIMLESS

FINISHING AVAILABLE

WH BK



| Code | Finishing | LED type | Power | Input voltage | Output current/voltage driver | Driver | LED flux | System flux | CCT | CRI | Optics | Weight |
|-------------------|-----------|-------------|-------|---------------|-------------------------------|----------|----------|-------------|-------|-----|--------|-----------------|
| GLR02WW WH | WH | COB CITIZEN | 1x13W | 220-240V AC | 350 mA / 25-40V DC | Included | 1190 lm | 663 lm | 3000K | 90 | 20° | Ø85 mm, 0,23 kg |
| GLR02WW BK | BK | COB CITIZEN | 1x13W | 220-240V AC | 350 mA / 25-40V DC | Included | 1190 lm | 663 lm | 3000K | 90 | 20° | Ø85 mm, 0,23 kg |



see also **xglow surface**
at page 330