

PANDORA

758B-L33R2B-01



Recessed ceiling PANDORA IP44 Dali, Push LED COB 21W 1850lm CRI85 4000K 86° White

indelu³

PANDORA is the family of LED recessed ceiling lights with three sizes / powers in a circular version and two square. Its IP44 reinforces its versatility. Adjustability.

GENERAL DATA

Category	Recessed
Family	Pandora
Finish	[01] White
Location	Indoor
Installation	Ceiling
Body material	Aluminum
Diffuser material	Prismatic glass
Frame material	Aluminum
Reflector material	Faceted aluminum
ETIM class	EC001744
EAN	8433264016128

LIGHT SOURCES

LED COB	
Luminous flux	1850lm
Light source power	21 W
Color temperature	4000K
CRI	85
Color consistency	4 SDCM
Energy efficiency	A+ (4000K)

LIGHT BEAMS


Beam	86° - Direct symmetric
------	------------------------

TECHNICAL DATA

Dimensions	Height x Width x Length (mm): 195 x 195 x 60
IP	IP44
Protection class	Class II
Frequency	50/60 Hz
Dimmable	Dali, Push
Input voltage	220-240V AC V
Output current	500 mA
Power factor	0.95
Lifetime	50,000 h
LED lifetime L	80
LED lifetime B	20
Weight	1.3 Kg
Cut hole dimensions	Diameter (mm): 176
ECORAE category I	LED-B

NOTES

Finishes upon request: Black, Grey



PANDORA

758B-L33R2B-01



Recessed ceiling PANDORA IP44 Dali,Push LED COB 21W 1850lm CRI85 4000K 86° White

indeluž

PHOTOMETRIC DATA

