

Wall recessed IOTA LED SMD 25W 2925lm CR180 3000K 90° White

indeluž

IOTA is a collection of LED recessed wall getting a uniform bathroom floor. Four sizes, two color temperatures and adjustment option built make this an ideal lighting solution for any hall or staircase.

GENERAL DATA

Category	Recessed
Family	Iota
Finish	[01] White
Location	Indoor
Installation	Wall
Body material	Aluminum
Diffuser material	Opal methacrylate
Frame material	Aluminum
Reflector material	Painted aluminum
ETIM class	EC000481
EAN	8433264073565



LIGHT SOURCES

LED SMD

Luminous flux	2925lm
Light source power	25 W
Color temperature	3000K
CRI	80
Color consistency	4 SDCM
Energy efficiency	A++ (3000K), A+ (3000K), A (3000K)



LIGHT BEAMS

Beam	90° - Direct asymmetric
------	-------------------------

TECHNICAL DATA

Dimensions	Height x Width x Length (mm): 100 x 41 x 900
IP	IP20
Protection class	Class II
Frequency	50/60 Hz
Input voltage	220-240V AC V
Output current	700 mA
Power factor	0.9
Auxiliary gear	Electronic
Lifetime	60,000 h
LED lifetime L	80
LED lifetime B	20
Weight	1.35 Kg
Cut hole dimensions	Length x Width x Depth (mm): 890 x 90 x 41
ECORAE category I	LED-B

NOTES

Asymmetric
Not suitable for brick wall or concrete



Wall recessed IOTA LED SMD 25W 2925lm CRI80 3000K 90° White

indeluž

PHOTOMETRIC DATA

