

Recessed ceiling tilt NOK1 Orientable Dali LED COB 12.30W 1460lm CRI90 2700K 60° - White White

indeluž

NOK is the most comprehensive family of recessed LED responding to any need you can ask a recessed luminaire reduced in size. Thus, the NOK family has been developed in two designs, one round and one square and three versions: fixed, adjustable and rotational. This LED luminaire symmetrical or asymmetrical beam may be configured with frame, mini-frame or trimless, and provides two color temperatures and different powers.


GENERAL DATA

Category	Recessed
Family	Nok1
Finish	[01] White/[01] White
Location	Indoor
Installation	Ceiling
Body material	Aluminum, Polycarbonate
Diffuser material	Transparent polycarbonate
Frame material	Aluminum
Reflector material	Metallic polycarbonate
ETIM class	EC001744
EAN	8433264125431



LIGHT SOURCES

LED COB	
Luminous flux	1460lm
Light source power	12.3 W
Color temperature	2700K
CRI	90
Color consistency	3 SDCM
Energy efficiency	A++ (2700K), A+ (2700K)



LIGHT BEAMS

Beam	60° - Direct symmetric
------	------------------------

TECHNICAL DATA

Dimensions	Height x Diameter (mm): 92 x 80
IP	IP20
Protection class	Class II
Frequency	50/60 Hz
Dimmable	Dali
Input voltage	110-240V AC V
Output current	350 mA
Power factor	0.95
Sensors	-
Lifetime	55,000 h
LED lifetime L	90
LED lifetime B	10
Weight	0.35 Kg
Tilt angle	30.0 °
Cut hole dimensions	Diameter x Depth (mm): 72 x 92
ECORAE category I	LED-A

NOTES



NOK1

823A-L3813A6D-01-01



Recessed ceiling tilt NOK1 Orientable Dali LED COB 12.30W 1460lm CRI90 2700K 60° - White White

indeluž

Orientable

PRODUCTS OF THE SAME FAMILY



Nok1 Round Trim Tilt
CC