

### Recessed ceiling tilt NOK1 Orientable Dali LED COB 12.30W 1510lm CRI90 3000K 60° - White Gold

indeluž

NOK is the most comprehensive family of recessed LED responding to any need you can ask a recessed luminaire reduced in size. Thus, the NOK family has been developed in two designs, one round and one square and three versions: fixed, adjustable and rotational. This LED luminaire symmetrical or asymmetrical beam may be configured with frame, mini-frame or trimless, and provides two color temperatures and different powers.

#### GENERAL DATA

Category	Recessed
Family	Nok1
Finish	[01] White/[47] Gold
Location	Indoor
Installation	Ceiling
Body material	Aluminum, Polycarbonate
Diffuser material	Transparent polycarbonate
Frame material	Aluminum
Reflector material	Metallic polycarbonate
ETIM class	EC001744
EAN	8433264131036




#### LIGHT SOURCES

LED COB	
Luminous flux	1510lm
Light source power	12.3 W
Color temperature	3000K
CRI	90
Color consistency	3 SDCM
Energy efficiency	A++ (3000K), A+ (3000K)

#### LIGHT BEAMS

Beam	60° - Direct symmetric
------	------------------------



#### TECHNICAL DATA

Dimensions	Height x Diameter (mm): 92 x 80
IP	IP20
Protection class	Class II
Frequency	50/60 Hz
Dimmable	Dali
Input voltage	110-240V AC V
Output current	350 mA
Power factor	0.95
Sensors	-
Lifetime	55,000 h
LED lifetime L	90
LED lifetime B	10
Weight	0.35 Kg
Tilt angle	30.0 °
Cut hole dimensions	Diameter x Depth (mm): 72 x 92
ECORAE category I	LED-A

#### NOTES



# NOK1

823C-L3913A6D-01-47



Recessed ceiling tilt NOK1 Orientable Dali LED COB 12.30W 1510lm CRI90 3000K 60° - White Gold

indeluž

Orientable

## PRODUCTS OF THE SAME FAMILY



Nok1 Round Trim Fix  
CC



Nok1 Round Trim Tilt  
CC