

NOK is the most comprehensive family of recessed LED responding to any need you can ask a recessed luminaire reduced in size. Thus, the NOK family has been developed in two designs, one round and one square and three versions: fixed, adjustable and rotational. This LED luminaire symmetrical or asymmetrical beam may be configured with frame, mini-frame or trimless, and provides two color temperatures and different powers.

GENERAL DATA

| | |
|--------------------|---------------------------|
| Category | Recessed |
| Family | Nok1 |
| Finish | [02] Black/[47] Gold |
| Location | Indoor |
| Installation | Ceiling |
| Body material | Aluminum, Polycarbonate |
| Diffuser material | Transparent polycarbonate |
| Frame material | Aluminum |
| Reflector material | Metallic polycarbonate |
| ETIM class | EC001744 |
| EAN | 8433264131722 |

LIGHT SOURCES

| | |
|--------------------|-------------------------|
| LED COB | |
| Luminous flux | 1610lm |
| Light source power | 12.3 W |
| Color temperature | 4000K |
| CRI | 90 |
| Color consistency | 3 SDCM |
| Energy efficiency | A++ (4000K), A+ (4000K) |


LIGHT BEAMS

| | |
|------|------------------------|
| Beam | 25° - Direct symmetric |
|------|------------------------|

TECHNICAL DATA

| | |
|---------------------|---------------------------------|
| Dimensions | Height x Diameter (mm): 92 x 80 |
| IP | IP20 |
| Protection class | Class II |
| Frequency | 50/60 Hz |
| Dimmable | Dali |
| Input voltage | 110-240V AC V |
| Output current | 350 mA |
| Power factor | 0.95 |
| Sensors | - |
| Lifetime | 55,000 h |
| LED lifetime L | 90 |
| LED lifetime B | 10 |
| Weight | 0.35 Kg |
| Tilt angle | 30.0 ° |
| Cut hole dimensions | Diameter x Depth (mm): 72 x 92 |
| ECORAAE category I | LED-A |

NOTES



NOK1

823C-L4013A2D-02-47



Recessed ceiling tilt NOK1 Orientable Dali LED COB 12.30W 1610lm CRI90 4000K 25° - Black Gold

indeluž

Orientable

PRODUCTS OF THE SAME FAMILY



Nok1 Round Trim Fix
CC



Nok1 Round Trim Tilt
CC